






Interface FLOR | New Horizons







**SPECIFICATION**

<b>Product definition</b>	Tufted Plain Level Loop Tile	<b>Style number</b>	<b>6055200005</b>
<b>Pile Material</b>	100% BCF Solution Dyed Nylon	<b>Wear Classification</b>	Heavy Contract / U3P3
<b>Pile Yarn Weight</b>	550 g/m <sup>2</sup> ± 5%	<b>Radiant panel</b>	Cfl s1 (EN ISO 13501)
<b>Effective pile yarn weight</b>	345 g/m <sup>2</sup> ± 7.5%	<b>Hot Metal Nut</b>	Pass, low radius of ignition (BS 4790)
<b>Total Weight</b>	4200 g/m <sup>2</sup> ± 5%	<b>Castor Chair Rating</b>	≥ 2.4
<b>Pile Height</b>	2.3 mm ± 0.3 mm	<b>Dimensional Stability</b>	≤ 0.2%
<b>Total Thickness</b>	5.6 mm ± 0.3 mm	<b>Vertical Electrical Resistance</b>	5 x 10 <sup>5</sup> Ω < 1 x 10 <sup>6</sup> Ω Computerguard (ISO 10965)
<b>Gauge/Ends per 10cm</b>	1/10 - 41	<b>Colour Fastness - Light</b>	Light (ISO 105-B02) > 6-7
<b>Tufts per m<sup>2</sup></b>	184,500 ± 5%	<b>Tiles per Box</b>	20 - 5 (50 cm x 50 cm ± 0.2 %)
<b>Backing Type</b>	Graphlex®		

CE  
0336-CPD-8538  
EN 14041:2004

Monolithic Quarter Turn


**Mission Zero:**  
our promise to eliminate  
any negative impact our company  
may have on the environment  
by the year 2020.

[www.interfaceflor.eu](http://www.interfaceflor.eu)

Interface Europe Ltd reserve the right to change or modify specifications